



Subject Index to Volume 44

- Acid stress corrosion (of GRP), 137
- Adhesion, 185, 351
- Adhesion (fibre/matrix), 333
- Amine grafting (on carbon fibres), 333
- Anodic oxidation (pitch fibres), 351
- Aramid fibre composites, 333
- Argon plasmas, 333
- Asymptotic expansion, 369
- Average value, 145

- Bending stiffness, 21
- Buckling, 57

- Carbon fibre composites (CFRP), 333, 361
- Characteristic dimension, 13
- Characteristic strength ratio, 1
- CMCs, 257, 271
- Compliance saturation, 43
- Compression strength, 57
- Conducting fibres, 29
- Crack initiation (matrix), 257, 271
- Cracking mechanisms, 257, 271
- Creep resistance, 287
- Critical scale, 145
- Cross-ply laminates, 361
- Curing stresses, 361

- Damage (in GRP pipes), 137
- Damage mechanics, 159, 169, 299, 309
- Damage prediction, 169
- Damage zone, 1
- Debonding, 215
- Delamination matrix cracking, 159
- Design (with effective moduli), 145
- Dilute concentrations of inclusions, 287
- Dilute fibre suspensions, 29
- DMA (dynamic mechanical analysis), 87
- Durability, 137

- Effective moduli, 145
- Electrochemical treatments, 351
- Embedded single fibre test, 215
- Expansion coefficient, 21

- Failure analysis, 227
- Failure criteria, 209, 227
- Failure mechanisms, 127, 137
- Fatigue damage mechanics, 169, 299, 309
- Fatigue damage model, 169
- FEA (See finite element analysis)
- Fibre breakage, 215
- Fibre coatings, 87

- Fibre surface treatments, 185, 333, 351
- Finite element analysis (FEA), 215, 299, 309
- Free edge, 1
- Friction, 77

- Glass beads, 119

- High-modulus PE fibres, 127, 185, 197
- High-temperature deformation, 287
- Homogenization technique, 369
- Hybrid reinforcement, 119

- IITRI test, 57
- Impact, 151
- Impact behaviour, 107, 197
- Impact fatigue, 107
- Impact properties, 119
- Inclusion shape effect, 287
- Inhomogeneous bars, 21
- Integral transforms, 151
- Interface (fibre/matrix), 319
- Interfacial adhesion, 333
- Interfacial shear strength, 351
- Interference contrast microscopy, 127
- Internal stresses, 361
- Interphase, 87, 215, 319
- Isochronous compliance, 43

- Kevlar fibre composites (See aramid)

- Laminated metal composite, 71
- Linear and non-linear failure analysis, 227
- Local properties, 319
- Longitudinal stiffness, 21

- Material characterization, 57
- Matrix cracking, 95, 159, 257, 271
- Mechanical conditioning, 43
- Mechanical properties, 119,
- Metal matrix composites (MMCs), 71, 287, 369
- Micro-cracking, 95
- Microscopy studies, 127
- MMCs (See metal matrix composites)

- Non-linear mechanisms, 369
- Non-uniform elastic field, 145
- Notch sensitivity, 13
- Notch strength, 1, 13
- Notches, 159, 169

- Operational composite model, 43
- Orientation, 29
- Orthotropic width correction, 1
- Oxygen plasma treatment (PE fibres), 185
- Oxygen plasmas, 333

- Particle strengthening, 287
- Permittivity, 29
- Phenolic matrix (modified), 77
- Plasma surface treatments, 333
- Plasma treatment (PE fibres), 185
- Polyethylene fibre composites, 197
- Polyethylene fibres, 127, 185, 197
- Polynomial strength theories, 209
- Post-fatigue stiffness, 159
- Post-fatigue strength, 159
- Pre-stressing, 361
- Prediction (of post-fatigue strength), 299, 309
- Pres-stress effects, 369
- Propagator matrix, 151

- Random fibre composites, 43
- Residual thermal stress, 95

- Sewer linings (GRP), 137
- Short-fibre composites, 43
- Simulation model (matrix cracking), 257, 271
- Single fibre fragmentation test, 215
- Sliding velocity, 77
- Sliding wear, 77
- Spheroidal inclusions, 287
- Splitting, 159
- Stacking sequence, 13
- Strain energy release rate, 215
- Strength theories, 209
- Stress analysis, 57
- Stress concentration, 71
- Stress corrosion (of GRP), 137
- Stress trajectories, 43
- Stress transfer, 215
- Structure, 29
- Surface treatments (See fibre surface treatments)

- Tensorial polynomials, 209
- Thermal analysis, 87
- Thermal displacements, 319
- Thermal expansion, 95
- Thermal expansion coefficient, 21
- Thermal stresses, 71
- Thermoelastic properties, 95
- Thermoplastic matrix composites, 119

- | | | |
|---|-------------------------|-----------------------------|
| Transient creep, 287 | Un-notched strength, 13 | Wave propagation, 151, 369 |
| Transient waves, 151 | | Wear behaviour, 77 |
| Transverse cracks, 361 | | Whisker reinforcements, 369 |
| Transverse shear (effect on failure), 227 | Viscoelasticity, 43 | Width correction factor, 1 |
| | | Woven fabric, 13 |
| | | Woven roving composites, 77 |



Author Index to Volume 44

- | | | | |
|---------------------------------------|---------------------------|------------------------------------|-------------------------|
| Accorsi, M. L. 215 | Jang, B. P. 107 | Pan, H. M. 71 | Sturman, P. C. 29 |
| Adams, D. F. 351 | Jang, B. Z. 107, 333 | | |
| Ashby, M. F. 169 | Jones, F. R. 137 | | |
| | | Pang, M. K. M. 127 | Tan, S. C. 57 |
| Barsoum, M. W. 257, 271 | Kameswara, C. V. S. 77 | Peters, P. W. M. 43 | Thomason, J. L. 87 |
| Beakou, A. 369 | Kangutkar, P. 257 | Pollard, G. 185, 197 | Tissington, B. 185, 197 |
| Beaumont, P. W. R. 159, 169, 299, 309 | King, T. R. 351 | | Touratier, M. 369 |
| Buttry, D. A. 351 | Kowbel, W. 107 | Qiu, Y. P. 287 | Tsui, S. W. 137 |
| | | | |
| Chatellier, J. Y. 369 | Ladizesky, N. H. 127 | Rapp, H. 21 | Verma, A. P. 77 |
| | Lee, S. 71 | Reddy, J. N. 227 | Vishnawanath, B. 77 |
| | | Reddy, Y. S. N. 227 | |
| DiAnselmo, A. 215 | Marci, G. 43 | Rogerson, G. A. 151 | Wang, A. S. D. 257, 271 |
| DiBenedetto, A. T. D. 215 | Marissen, R. 361 | | Wang, Y. M. 287 |
| Donoghue, R. D. 43 | McCullough, R. L. 29, 319 | Schulte, K. 361 | Ward, I. M. 185, 197 |
| | Milosavljevic, D. I. 151 | Scott, W. R. 319 | Weng, G. J. 287 |
| | | Shembekar, P. 1, 13 | Wilczynski, A. P. 209 |
| Green, W. A. 151 | | Smith, P. A. 309 | Wolfenstine, J. 71 |
| Gudmundson, P. 95 | Naik, N. K. 1, 13 | Sottos, N. R. 319 | |
| | | Spearing, S. M. 159, 169, 299, 309 | Ye, L. 145 |
| Huang, X. G. 271 | Ostlund, S. 95 | | Yilmazer, U. 119 |